

Material Safety Data Sheet

Page 1 of 3

Infosafe No. 2BKM8 Issue Date: August 2003 ISSUED by BOSTIK

Product Name: **SIMSON ISR 7001**

Not classified as hazardous according to criteria of NOHSC

COMPANY DETAILS

Company Name BOSTIK FINDLEY AUSTRALIA PTY LTD (ABN 003 893 838)
Address 51 - 71 High Street Thomastown
VIC 3074
Tel/Fax Tel: 03 9279 9333 Fax: 03 9279 9270

IDENTIFICATION

Product Name SIMSON ISR 7001

Other Names	Name	Mancode
	Simson ISR 7001 Black, 600 sg	286796
	Simson ISR 7001 Black, 290 Ctg	291862
	Simson ISR 7001 Grey, 290 Ctg	291846
	Simson ISR 7001 Grey, 600 sg	291854
	Simson ISR 7001 White, 290 Ctg	281166
	Simson ISR 7001 White, 600 sg	286435

UN Number None Allocated
DG Class None Allocated
Packing Group None Allocated
Hazchem Code None Allocated
Poisons Schedule Not Scheduled
Product Use A sealant designed for automotive applications.

Physical Data

Appearance Colored paste with faint odour.
Boiling Point NA
Specific Gravity 1.4
Flash Point >100°C
Solubility in Water Insoluble

Other Properties

Autoignition Temp. >300°C

Ingredients

Ingredients	Name	CAS	Proportion
	Diisononylphthalate		10-30 %
	Alkoxysilane		1-5 %

HEALTH HAZARD INFORMATION

Health Effects

Acute - Swallowed May be harmful if swallowed.
Acute - Eye May be an eye irritant.
Acute - Skin Contact with skin may result in irritation.
Acute - Inhaled During curing a small amount of methanol is released. Inhalation of methanol vapours can cause headache, nausea and respiratory irritation.
Chronic Repeated or prolonged skin contact may cause irritation.

First Aid

Swallowed If swallowed, seek immediate medical advice.
Eye Hold eyelids open and immediately flush with plenty of water for at least 15 minutes. Seek medical attention.

Continued on next page

Material Safety Data Sheet

Page 2 of 3

Infosafe No. 2BKM8 Issue Date: August 2003

ISSUED by BOSTIK

Product Name: **SIMSON ISR 7001**

Not classified as hazardous according to criteria of NOHSC

Skin Remove contaminated clothing and footwear. Wash affected skin thoroughly with soap and water. If irritation persists, seek medical attention. Wash clothing before re-use.

Inhaled Remove patient to fresh air. Apply artificial respiration if necessary. Seek medical advice.

First Aid Facilities eye wash

Advice to Doctor

Advice to Doctor Treat symptomatically.

Other Health Hazard Information

PRECAUTIONS FOR USE

Exposure Limits No exposure standard is available for the material as such. Exposure standards available for the components are as follows:
alkoxysilane TWA: 5ppm,
diisononylphthalate TWA: 5mg/m³
methanol (trace given off during curing) TWA: 200ppm (262mg/m³), 250ppm (328mg/m³)-Skin
TWA is the time weighted average concentration of the work atmosphere over anormal 8-hour work day and a 40-hour work week. Nearly all workers may be repeatedly exposed to this level, day after day, without adverse effect. These TWAs are issued as guidelines for good practice. All atmospheric contamination should be kept to as low a level as is practically possible. These TWAs should not be used as fine lines between safe and dangerous concentrations.

Eng. Controls Ventilation should be sufficient to ensure exposure to vapours is as low as practicable or at least below the recommended exposure standards.

Personal Protection

Protective Equip. Avoid contact with skin and eyes and avoid breathing vapours. The following personal protective equipment is recommended:
Respiratory protection such as air supplied breathing apparatus or suitable organic vapour cartridge mask (complying with Australian Standards AS1715 & AS1716) required in poorly ventilated areas.
Chemical resistant gloves for repeated or prolonged skin contact.
Safety glasses if risk of material entering the eyes.

Flammability

SAFE HANDLING INFORMATION

Storage and Transport

Storage and Transport Store under cool, dry conditions in original container.

Spills and Disposal

Spills & Disposal Clean-up personnel to wear appropriate protective equipment. Collect spill into clearly labelled, sealable containers for disposal as per statutory regulations. Clean area with water and detergent.

Fire/Explosion Hazard

Fire/Explos. Hazard Hazardous decomposition products on burning: oxides of carbon, smoke and fumes.
Fire-fighting personnel to wear self-contained breathing apparatus and protective clothing.
Extinguishing media: foam, dry chemical, carbon dioxide.
Prevent fire fighting run off from entering the drains and water-ways.

Hazchem Code None Allocated

Continued on next page

Material Safety Data Sheet

Page 3 of 3

Infosafe No. 2BKM8 Issue Date: August 2003

ISSUED by BOSTIK

Product Name: **SIMSON ISR 7001**

Not classified as hazardous according to criteria of NOHSC

OTHER INFORMATION

Environ. Protection This material may be hazardous to the environment, do not discharge to drains or water-ways.

Technical Data Refer Product Information Bulletin

Other Information N/A - None Assigned
NOHSC - National Occupational Health & Safety Commission (Worksafe Aust.)

CONTACT POINT

Contact & 24 hour Emergency Telephone
Regulatory Affairs Officer
ph (03) 9279 9320 or
mobile 0419 335 187
...End Of MSDS...